

Wall mount bracket for DWC-XPZA cameras

DWC-XPZAWM



WHAT'S IN THE BOX

1x Machine Screw, HM3 x 8 (Adapter Screw)

1x Silicon Cap (30 x 11mm)

1x O-Type Waterproof Ring (1.5 x 2mm)

1x Waterproof Mounting Pad (167 x 122 x 41.5mm)

4x Tapping Mounting Screws

1x Quick Setup Guide

NOTE: Download all your support materials and tools in one place.

1. Go to: <http://www.digital-watchdog.com/resources>
2. Search your product by entering the part number in the **'Search by Product'** search bar. Results for applicable part numbers will populate automatically based on the part number you enter.
3. Click **'Search'**. All supported materials, including manuals and quick start guide (QSGs) will appear in the results.



INSTALLATION

- 1 Mark and drill the necessary holes on the mounting surface using the mounting bracket itself.
- 2 Secure the mounting bracket to the mounting surface using the tapping screws included with the mount. Use the waterproof mounting pad between the bracket's arm and the mounting surface as needed.
- 3 Attach the bracket adapter included with the camera to the wall mount. Use the machine screw included with the mount to secure the adapter to the mounting bracket. Place the O ring between the wall mount and camera adapter to prevent moisture accessing the camera.
- 4 Secure the camera to the wall mount with the safety wire included with the camera.
- 5 Pass wires through and make all necessary connections. If you are running the cables from the wall behind the mount, use the silicon cap to seal the pipe at the bottom of the mount.
- 6 Secure the camera to the adapter using the screws included with the camera to complete the installation.

